

ACRYLIC FLAT LATEX HOUSE PAINT, 103A131 Safety Data Sheet

ACE HARDWARE CORP, PAINT DIVISION -- ACRYLIC FLAT LATEX HOUSE PAINT,
103A131 -- 8010-00N053415

=====
Product Identification
=====

Product ID:ACRYLIC FLAT LATEX HOUSE PAINT, 103A131
MSDS Date:01/29/1996
FSC:8010
NIIN:00N053415
MSDS Number: CFPBX
=== Responsible Party ===
Company Name:ACE HARDWARE CORP, PAINT DIVISION
Address:21901 S CENTRAL AVE
City:MATTESON
State:IL
ZIP:60443
Country:US
Info Phone Num|:708-720-0600
Emergency Phone Num:708-990-6600
CAGE:ACEHA
=== Contractor Identification ===
Company Name:ACE HARDWARE CORPORATION
Address:21901 SOUTH CENTRAL AVENUE
City:MATTESON
State:IL
ZIP:60443
Country:US
Phone:708-720-0600
CAGE:ACEHA

=====
Composition/Information on Ingredients
=====

Ingred Name:TITANIUM OXIDE; (TITANIUM DIOXIDE)
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 24.9%
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST

Ingred Name:NEPHELINE SYENITE
CAS:37244-96-5
Fraction by Wt: 28.8%
OSHA PEL:N/K
ACGIH TLV:5 MG/M3 (MFR)

Ingred Name:SILICA, AMORPHOUS, DIATOMACEOUS EARTH; (DIATOMACEOUS EARTH)
CAS:61790-53-2
RTECS #:VV7311000
Fraction by Wt: 2.8%
OSHA PEL:20 MPPCF
ACGIH TLV:10 MG/M3 TDUST

Ingred Name:SILICA GEL; (AMORPHOUS SILICA)
CAS:112945-52-5
RTECS #:VV7310000

Fraction by Wt: 1.2%
OSHA PEL:6 MG/M3
ACGIH TLV:10 MG/M3

Ingred Name:1,2-PROPANEDIOL; (PROPYLENE GLYCOL)
CAS:57-55-6
RTECS #:TY2000000
Fraction by Wt: 2.3%
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:IRON (III) OXIDE; (IRON OXIDE)
CAS:1309-37-1
RTECS #:NO7400000
Fraction by Wt: 6%
OSHA PEL:10 MG/M3 (FE)
ACGIH TLV:5 MG/M3 FUME (FE)

Ingred Name:IRON HYDROXIDE OXIDE; (HYDRATED IRON OXIDE)
CAS:20344-49-4
Fraction by Wt: 3.9%
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:AMMONIA (SARA 302/313) (CERCLA)
CAS:7664-41-7
RTECS #:BO0875000
Fraction by Wt: <0.1%
OSHA PEL:50 PPM
ACGIH TLV:25 PPM;35 STEL
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:ALUMINUM HYDROXIDE
CAS:21645-51-2
RTECS #:BD0940000
Fraction by Wt: 0.9%
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:PALYGORSKITE; (MAGNESIUM ALUMINUM SILICATE)
CAS:12174-11-7
RTECS #:RT6400000
Fraction by Wt: 0.3%
OSHA PEL:15 MG/M3 (MFR)
ACGIH TLV:10 MG/M3 (MFR)

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-REFINED
(SEVERE) HEAVY PARAFFINIC; (ALIPHATIC PETROLEUM DISTILLATE)
CAS:64741-88-4
RTECS #:PY8040501
Fraction by Wt: 0.5%
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:CARBAMIC ACID, BUTYL-, 3-iodo-2-propynyl ester;
(3-iodo-2-propynyl butyl carbamate)

CAS:55406-53-6
RTECS #:EZ0950000
Fraction by Wt: 0.3%
OSHA PEL:N/K
ACGIH TLV:N/K

=====
Hazards Identification
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:IN A CONFINED AREA VAPORS IN
HIGH CONCENTRATION ARE ANESTHETIC. IRRITANT TO UPPER RESPIRATORY
SYSTEM. CHRONIC:PROBLEMS WITH RESPIRATORY SYSTEM MAY BE AGGRAVATED
BY EXPOSURE TO VAPORS.
Explanation of Carcinogenicity:NOT RELEVANT
Effects of Overexposure:LIGHTHEADEDNESS AND STAGGERED GAIT.
Medical Cond Aggravated by Exposure:CHRONIC PROBLEMS W/RESPIRATORY
SYSTEM MAY BE AGGRAVATED BY EXPOSURE TO VAPORS.

=====
First Aid Measures
=====

First Aid:INGEST:CALL MD IMMEDIATELY . INHAL:REMOVE FROM EXPOSURE -
RESTORE BREATHING - KEEP WARM & QUIET. SKIN:WASH W/SOAP & WATER.
LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. EYES:FLUSH W/WATER FOR
AT L EAST 15 MINUTES. GET MEDICAL AID.

=====
Fire Fighting Measures
=====

Flash Point Method:PMCC
Flash Point:199F,93C
Extinguishing Media:NON-COMBUSTIBLE - FOR DRY SOLIDS USE WATER, FOAM,
CO*2, DRY CHEMICALS.
Fire Fighting Procedures:USE NIOSH APPROVED SCBA & FULL PROTECTIVE
EQUIPMENT . WATER MAY BE USED TO COOL CLOSED CONTAINERS.
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO EXTREME HEAT
MAY RUPTURE DUE TO PRESSURE BUILD-UP. CONTENTS MAY SPATTER IF
TEMPERATURE EXCEEDS 212F.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE &
REMOVE W/INERT ABSORBENT.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage
=====

Handling and Storage Precautions:DOL STORAGE CATEGORY 3B. AVOID
BREATHING VAPOR OR SPRAY MIST. AVOID CONTACT W/SKIN OR EYES.
Other Precautions:KEEP OUT OF REACH OF CHILDREN.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:RESPIRATORY DEVICE APPROVED BY NIOSH.
Ventilation:LOCAL EXHAUST:PREFERABLE. MECHANICAL (GENERAL):ACCEPTABLE.
Protective Gloves:IMPERVIOUS GLOVES .
Eye Protection:ANSI APPROVED CHEM WORKERS GOGGS .

Other Protective Equipment:EYE WASH FOUNTAIN & DELUGE SHOWER WHICH MEET
ANSI DESIGN CRITERIA .

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212F,100C

Vapor Density:HVR/AIR

Spec Gravity:1.26 (H*20=1)

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:DILUTABLE

Appearance and Odor:COLORED PIGMENTED LIQUID W/SLIGHT AMMONIA ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NO HAZARDOUS REACTIONS ARE EXPECTED UNDER NORMAL USE.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:CARBON DIOXIDE & CARBON MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN APPROVED FACILITY. DO NOT
INCINERATE CLOSED CONTAINERS. DISPOSE OF I/A/W FEDERAL, STATE &
LOCAL REGULATIONS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular