

## Section 1. Identification

Product name Dual Range HV 32  
 SDS # 460274  
 Code 460274-US06

### Relevant identified uses of the substance or mixture and uses advised against

**Product use** Hydraulic fluid  
 For specific application advice see appropriate Technical Data Sheet or consult our company representative.

**Manufacturer** Castrol Industrial North America, Inc.  
 150 W. Warrenville Road  
 Naperville, IL 60563

**Supplier** Castrol Industrial North America, Inc.  
 150 W. Warrenville Road  
 Naperville, IL 60563  
 Product Information: +1-877-641-1600

**EMERGENCY SPILL INFORMATION:** 1 (800) 424-9300 CHEMTREC (USA)

## Section 2. Hazards identification

**OSHA/HCS status** This material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Classification of the substance or mixture** Not classified.

### GHS label elements

**Signal word** No signal word.  
**Hazard statements** No known significant effects or critical hazards.

### Precautionary statements

**Prevention** Not applicable.  
**Response** Not applicable.  
**Storage** Not applicable.  
**Disposal** Not applicable.

**Hazards not otherwise classified** Defatting to the skin.  
 Note: High Pressure Applications  
 Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency.  
 See 'Notes to physician' under First-Aid Measures, Section 4 of this Safety Data Sheet.

## Section 3. Composition/information on ingredients

Highly refined mineral oil and additives

**Substance/mixture** Mixture

Ingredient name	CAS number	%
Distillates (petroleum), hydrotreated, heavy paraffinic	64742-54-7	≥50 - <75
Base oil - highly refined	Varies	≥25 - <50

**Product name** Dual Range HV 32 **Product code** 460274-US06 **Page:** 1/9  
**Version** 1.01 **Date of issue** 06/05/2015. **Format** US **Language** ENGLISH  
 (US) (ENGLISH)

## Section 3. Composition/information on ingredients

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur.
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training.

### Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treatment should in general be symptomatic and directed to relieving any effects.

Note: High Pressure Applications

Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. Injuries may not appear serious at first but within a few hours tissue becomes swollen, discolored and extremely painful with extensive subcutaneous necrosis.

Surgical exploration should be undertaken without delay. Thorough and extensive debridement of the wound and underlying tissue is necessary to minimize tissue loss and prevent or limit permanent damage. Note that high pressure may force the product considerable distances along tissue planes.

Specific treatments No specific treatment.

## Section 5. Fire-fighting measures

### Extinguishing media

Suitable extinguishing media	In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.
Unsuitable extinguishing media	Do not use water jet.
Specific hazards arising from the chemical	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	Combustion products may include the following: carbon dioxide carbon monoxide
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Product name	Dual Range HV 32	Product code	460274-US06	Page: 2/9
Version	1.01	Date of issue	06/05/2015.	Format US
				(US)
				Language ENGLISH
				(ENGLISH)

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

<b>For non-emergency personnel</b>	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.
<b>For emergency responders</b>	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
<b>Environmental precautions</b>	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

<b>Small spill</b>	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
<b>Large spill</b>	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

## Section 7. Handling and storage

### Precautions for safe handling

<b>Protective measures</b>	Put on appropriate personal protective equipment (see Section 8).
<b>Advice on general occupational hygiene</b>	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
<b>Conditions for safe storage, including any incompatibilities</b>	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.
<b>Not suitable</b>	Prolonged exposure to elevated temperature

## Section 8. Exposure controls/personal protection

### Control parameters

### Occupational exposure limits

<b>Ingredient name</b>	<b>Exposure limits</b>
Distillates (petroleum), hydrotreated, heavy paraffinic	<b>ACGIH TLV (United States).</b> TWA: 5 mg/m <sup>3</sup> 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction <b>OSHA PEL (United States).</b> TWA: 5 mg/m <sup>3</sup> 8 hours. Issued/Revised: 6/1993
Base oil - highly refined	<b>ACGIH TLV (United States).</b> TWA: 5 mg/m <sup>3</sup> 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction <b>OSHA PEL (United States).</b> TWA: 5 mg/m <sup>3</sup> 8 hours. Issued/Revised: 6/1993

**Product name** Dual Range HV 32

**Product code** 460274-US06

**Page:** 3/9

**Version** 1.01 **Date of issue** 06/05/2015.

**Format** US  
(US)

**Language** ENGLISH  
(ENGLISH)

## Section 8. Exposure controls/personal protection

While specific OELs for certain components may be shown in this section, other components may be present in any mist, vapor or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

<b>Appropriate engineering controls</b>	<p>All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.</p> <p>Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.</p> <p>The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.</p>
<b>Environmental exposure controls</b>	<p>Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.</p>
<b><u>Individual protection measures</u></b>	
<b>Hygiene measures</b>	<p>Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.</p> <p>Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.</p>
<b>Eye/face protection</b>	<p>Safety glasses with side shields.</p>
<b><u>Skin protection</u></b>	
<b>Hand protection</b>	<p>Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.</p> <p>Consult your supervisor or Standard Operating Procedure (S.O.P) for special handling instructions.</p>
<b>Body protection</b>	<p>Use of protective clothing is good industrial practice.</p> <p>Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.</p> <p>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</p>
<b>Other skin protection</b>	<p>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</p>
<b>Respiratory protection</b>	<p>In case of insufficient ventilation, wear suitable respiratory equipment.</p> <p>The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.</p>

## Section 9. Physical and chemical properties

### Appearance

Physical state	Liquid.
Color	Purple.
Odor	Not available.
Odor threshold	Not available.
pH	Not available.
Melting point	Not available.
Boiling point	Not available.
Flash point	Open cup: 175°C (347°F) [Cleveland.]
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable. Based on - Physical state
Lower and upper explosive (flammable) limits	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Density	<1000 kg/m <sup>3</sup> (<1 g/cm <sup>3</sup> ) at 15°C
Solubility	insoluble in water.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Kinematic: 29 to 35 mm <sup>2</sup> /s (29 to 35 cSt) at 40°C Kinematic: 6.8 mm <sup>2</sup> /s (6.8 cSt) at 100°C

## Section 10. Stability and reactivity

Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
Chemical stability	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerization will not occur.
Conditions to avoid	Avoid all possible sources of ignition (spark or flame).
Incompatible materials	Reactive or incompatible with the following materials: oxidizing materials.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Aspiration hazard

Name	Result
Distillates (petroleum), hydrotreated, heavy paraffinic	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure Routes of entry anticipated: Dermal, Inhalation.

#### Potential acute health effects

Eye contact No known significant effects or critical hazards.

Product name	Dual Range HV 32	Product code	460274-US06	Page:	5/9
Version	1.01	Date of issue	06/05/2015.	Format	US
				(US)	Language ENGLISH
					(ENGLISH)



## Section 11. Toxicological information

<b>Skin contact</b>	No known significant effects or critical hazards.
<b>Inhalation</b>	Vapor inhalation under ambient conditions is not normally a problem due to low vapor pressure.
<b>Ingestion</b>	No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

<b>Eye contact</b>	No specific data.
<b>Skin contact</b>	Adverse symptoms may include the following: irritation dryness cracking
<b>Inhalation</b>	No specific data.
<b>Ingestion</b>	No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

<b>Potential immediate effects</b>	Not available.
<b>Potential delayed effects</b>	Not available.

#### Long term exposure

<b>Potential immediate effects</b>	Not available.
<b>Potential delayed effects</b>	Not available.

#### Potential chronic health effects

<b>General</b>	No known significant effects or critical hazards.
<b>Carcinogenicity</b>	No known significant effects or critical hazards.
<b>Mutagenicity</b>	No known significant effects or critical hazards.
<b>Teratogenicity</b>	No known significant effects or critical hazards.
<b>Developmental effects</b>	No known significant effects or critical hazards.
<b>Fertility effects</b>	No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

Not available.

## Section 12. Ecological information

### Toxicity

No testing has been performed by the manufacturer.

### Persistence and degradability

Partially biodegradable.

### Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

### Mobility in soil

<b>Soil/water partition coefficient (<math>K_{oc}</math>)</b>	Not available.
<b>Mobility</b>	Spillages may penetrate the soil causing ground water contamination.

<b>Product name</b> Dual Range HV 32	<b>Product code</b> 460274-US06	<b>Page:</b> 6/9
<b>Version</b> 1.01	<b>Date of issue</b> 06/05/2015.	<b>Format</b> US
		<b>Language</b> ENGLISH
		(US)
		(ENGLISH)

## Section 12. Ecological information

<b>Other adverse effects</b>	No known significant effects or critical hazards.
<b>Other ecological information</b>	Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

## Section 13. Disposal considerations

<b>Disposal methods</b>	The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
-------------------------	--

## Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	IATA
<b>UN number</b>	Not regulated.	Not regulated.	Not regulated.	Not regulated.
<b>UN proper shipping name</b>		-	-	-
<b>Transport hazard class(es)</b>	-	-	-	-
<b>Packing group</b>	-	-	-	-
<b>Environmental hazards</b>	No.	No.	No.	No.
<b>Additional information</b>	-	-	-	-

**Special precautions for user** Not available.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not available.

## Section 15. Regulatory information

### U.S. Federal regulations

**United States inventory (TSCA 8b)** All components are listed or exempted.

### SARA 302/304

#### Composition/information on ingredients

No products were found.

### SARA 311/312

**Classification** Not applicable.

### SARA 313

<b>Product name</b> Dual Range HV 32	<b>Product code</b> 460274-US06	<b>Page:</b> 7/9
<b>Version</b> 1.01 <b>Date of issue</b> 06/05/2015.	<b>Format</b> US (US)	<b>Language</b> ENGLISH (ENGLISH)

## Section 15. Regulatory information

Form R - Reporting requirements	This product does not contain any hazardous ingredients at or above regulated thresholds.
Supplier notification	This product does not contain any hazardous ingredients at or above regulated thresholds.
<b>State regulations</b>	
Massachusetts	None of the components are listed.
New Jersey	The following components are listed: MINERAL OIL (UNTREATED and MILDLY TREATED); MINERAL OIL (UNTREATED and MILDLY TREATED)
Pennsylvania	None of the components are listed.
California Prop. 65	<b>WARNING:</b> This product contains a chemical known to the State of California to cause cancer. naphthalene; Ethyl acrylate
<b>Other regulations</b>	
Australia inventory (AICS)	All components are listed or exempted.
Canada inventory	All components are listed or exempted.
China inventory (IECSC)	All components are listed or exempted.
Japan inventory (ENCS)	At least one component is not listed.
Korea inventory (KECI)	All components are listed or exempted.
Philippines inventory (PICCS)	All components are listed or exempted.
Taiwan inventory (CSNN)	Not determined.
REACH Status	For the REACH status of this product please consult your company contact, as identified in Section 1.

## Section 16. Other information

### Hazardous Material Information System (U.S.A.)

Health	1
Flammability	1
Physical hazards	0
Personal protection	X

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

### National Fire Protection Association (U.S.A.)



### History

Date of issue/Date of revision	06/05/2015.
Date of previous issue	11/24/2014.
Key to abbreviations	ACGIH = American Conference of Industrial Hygienists ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor CAS Number = Chemical Abstracts Service Registry Number GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods

Product name	Dual Range HV 32	Product code	460274-US06	Page:	8/9
Version	1.01	Date of issue	06/05/2015.	Format	US (US)
				Language	ENGLISH (ENGLISH)



## Section 16. Other information

LogPow = logarithm of the octanol/water partition coefficient  
MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
OEL = Occupational Exposure Limit  
SDS = Safety Data Sheet  
STEL = Short term exposure limit  
TWA = Time weighted average  
UN = United Nations  
UN Number = United Nations Number, a four digit number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods.

☑ Indicates information that has changed from previously issued version.

### Notice to reader

*All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.*

*The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.*

*It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.*

Product name Dual Range HV 32

Product code 460274-US06

Page: 9/9

Version 1.01 Date of issue 06/05/2015.

Format US

Language ENGLISH

(US)

(ENGLISH)





## PRODUCT DATA

### Castrol Dual Range HV

Castrol Dual Range HV Hydraulic Fluids are exceptional multi-viscosity hydraulic fluids that provide proven anti-wear protection coupled with very shear stable polymers and anti-foam additives for a balanced package. An extreme load carrying capability is indicated where Castrol Dual Range HV Hydraulic Fluids pass the FZG Load carrying test at Stage 12. This outstanding performance provides the extra measure of protection required in high load applications such as hydrostatic transmissions and high speed/high pressure hydraulic circuits.

Castrol Dual Range HV Hydraulic Fluids' high viscosity indexes and their low pour points ensure extra pump protection and efficiency in cold weather starts and provide needed viscosity protection at higher operating temperatures. The products are dyed purple to facilitate leak detection.

### Features and Benefits

- Very shear stable polymers provide universal applications under a wide range of ambient conditions.
  - Excellent viscosity at operating temperatures (particularly under extreme conditions).
- Less wear promotes longer equipment life and better productivity through maximum hydraulic system efficiency.
- Excellent vane and piston pump performance that meets major hydraulic pump manufacturers' requirements.
  - Less failure of hydraulic circuits.
  - Less equipment repair for long term trouble-free service
- Outstanding hydrolytic stability provides additional protection against corrosion in the presence of water. Systems operate more efficiently, while reducing maintenance costs.
- Exceptional oxidation and thermal stability provides resistant to thermal degradation in the presence of entrained air and catalyzing metals.
  - Prevents the formation of sludge and varnish deposits during periods of extended high temperature operation.
- Resistant to the formation of oxidation acids allowing longer pump life, less wear, less down time

### Warranty and Protection Requirements

- Exceeds all manufacturer's warranty requirements for applications requiring a Dennison HF-O approved hydraulic fluid

### Industry Specifications and OEM Approvals by Grade

- Denison HF-O, HF-1, HF-2 Approved
- Vickers 35VQ25A - meets performance requirements
- Vickers M-2950-S Mobile Hydraulic Systems and I-286-S Industrial Hydraulic Systems
- Cincinnati Machine P-68 (ISO 32), P-70 (ISO 46) and P-69 (ISO 68) approved
- Meets Racine S106
- Meets Joy Mining Machinery HO-T (AW 46), HO-S (AW 68)
- Meets DIN 51524 Requirements



## Typical Properties\*

Test	Method	Typical Results				
		ISO Grade	32	46	68	100
Viscosity at 40° C, cSt	ASTM D-445		32.6	46.5	68	100.3
Viscosity at 100° C, cSt	ASTM D-445		6.2	7.9	10.6	13.9
Viscosity at 100F, SUS	ASTM D-2161		153	216	314	459
Viscosity at 210F, SUS	ASTM D-2161		47	52	61	73
Viscosity Index	ASTM D-2270		141	143	146	141
Flash Point, °C (°F)	ASTM D-92		210(410)	232(450)	240(464)	251(484)
Pour Point, °C (°F)	ASTM D-97		-51(-60)	-45(-49)	-39(-38)	-36(-33)
Dielectric Breakdown	ASTM D877		-	-	-	-
Voltage, KV/0.1 inch			-	35	-	-
Gravity, API	ASTM D-287		31.3	34	30	29
Specific Gravity @60F, g/ml	ASTM D-1298		7.24	7.12	7.3	7.34
Pounds per Gallon	ASTM D-287		0.869	0.859	0.874	0.88

\* Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.

## Part Numbers and UPCs

Grade	32	46	68	100
5 Gal. Pail Part No.	41557	42057	42257	
55 Gal. Drum Part No.	41559	42059	42259	42269
260 Gal. Tote Part No.	415547	420547	422547	
Bulk	41550	42050	42250	

## Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the applications referred to above and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDSs are available upon request through your sales contact office, or via the Internet at [www.castrol.com/us](http://www.castrol.com/us). This product should not be used for purposes other than the applications referred to above. If disposing of used product, take care to protect the environment, return used oil to collection center.

BP Lubricants USA Inc.  
 1500 Valley Road  
 Wayne, NJ 07470  
 Telephone: 1,800.462.0835  
 Email: [contactus@bp.com](mailto:contactus@bp.com)  
 ©2011 BP Lubricants USA Inc. All rights reserved.

[www.castrol.com/us](http://www.castrol.com/us)