

 Close this window

MSDS

Common Name: ICWB LSPR 12PK FLUOR GREEN MARKNG, 203032**Manufacturer:** RUST-OLEUM**MSDS Revision Date:** 8/26/2014**MSDS Format:** GHS-US**Grainger Item Number(s):** 6KP34**Manufacturer Model Number(s):**

MSDS Table of Contents

Click the desired link below to jump directly to that section in the MSDS.

- [1. IDENTIFICATION](#)
- [2. HAZARD IDENTIFICATION](#)
- [3. COMPOSITION/INFORMATION ON INGREDIENTS](#)
- [4. FIRST-AID MEASURES](#)
- [5. FIRE-FIGHTING MEASURES](#)
- [6. ACCIDENTAL RELEASE MEASURES](#)
- [7. HANDLING AND STORAGE](#)
- [8. EXPOSURE CONTROLS/PERSONAL PROTECTION](#)
- [9. PHYSICAL AND CHEMICAL PROPERTIES](#)
- [10. STABILITY AND REACTIVITY](#)
- [11. TOXICOLOGICAL INFORMATION](#)
- [12. ECOLOGICAL INFORMATION](#)
- [13. DISPOSAL INFORMATION](#)
- [14. TRANSPORT INFORMATION](#)
- [15. REGULATORY INFORMATION](#)
- [16. OTHER INFORMATION](#)

DATE PRINTED: 8/26/2014

SAFETY DATA SHEET

RUST-OLEUM CORPORATION

TRUSTED QUALITY SINCE 1921

WWW.RUSTOLEUM.COM

1. IDENTIFICATION

top

PRODUCT NAME: ICWB LSPR 12PK FLUOR GREEN MARKNG

PRODUCT IDENTIFIER: 203032

PRODUCT USE/CLASS: MARKING PAINT/AEROSOL

REVISION DATE: 8/26/2014

SUPERCEDES DATE: NEW SDS

SUPPLIER:

RUST-OLEUM CORPORATION

11 HAWTHORN PARKWAY

VERNON HILLS, IL 60061
USA

MANUFACTURER:
RUST-OLEUM CORPORATION
11 HAWTHORN PARKWAY
VERNON HILLS, IL 60061
USA

PREPARER: REGULATORY DEPARTMENT

EMERGENCY TELEPHONE:
24 HOUR HOTLINE: 847-367-7700

2. HAZARD IDENTIFICATION



EMERGENCY OVERVIEW:

HARMFUL IF SWALLOWED. EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPORS MAY CAUSE FLASH FIRE OR EXPLOSION. CONTENTS UNDER PRESSURE. HARMFUL IF INHALED. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. MAY CAUSE EYE, SKIN, OR RESPIRATORY TRACT IRRITATION. KEEP OUT OF REACH OF CHILDREN. HARMFUL IF INHALED. CAUSES EYE IRRITATION. USE VENTILATION NECESSARY TO KEEP EXPOSURES BELOW RECOMMENDED EXPOSURE LIMITS, IF ANY. VAPOR HARMFUL. CAUSES EYE, SKIN, NOSE, AND THROAT IRRITATION.

CLASSIFICATION:

SYMBOL(S) OF PRODUCT:
EXCLAMATION MARK
FLAME
HEALTH HAZARD

SIGNAL WORD: DANGER

GHS HAZARD STATEMENTS:

FLAMMABLE AEROSOL, CATEGORY 1:
H222: EXTREMELY FLAMMABLE AEROSOL.

FLAMMABLE LIQUID, CATEGORY 1:
H224: EXTREMELY FLAMMABLE LIQUID AND VAPOUR.

ACUTE TOXICITY, ORAL, CATEGORY 5:
H303: MAY BE HARMFUL IF SWALLOWED.

ACUTE TOXICITY, DERMAL, CATEGORY 5:
H313: MAY BE HARMFUL IN CONTACT WITH SKIN.

SKIN IRRITATION, CATEGORY 2:
H315: CAUSES SKIN IRRITATION.

EYE IRRITATION, CATEGORY 2:
H319: CAUSES SERIOUS EYE IRRITATION.

ACUTE TOXICITY, INHALATION, CATEGORY 4:
H332: HARMFUL IF INHALED.

STOT, SINGLE EXPOSURE, CATEGORY 3, RTI:
H335: MAY CAUSE RESPIRATORY IRRITATION.

STOT, SINGLE EXPOSURE, CATEGORY 3, NE:
H336: MAY CAUSE DROWSINESS OR DIZZINESS.

ASPIRATION HAZARD, CATEGORY 2:
H305: MAY BE HARMFUL IF SWALLOWED AND ENTERS AIRWAYS.

EYE IRRITATION, CATEGORY 2B:

H320: CAUSES EYE IRRITATION.

FLAMMABLE AEROSOL, CATEGORY 1:

H280: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED

GHS PRECAUTIONARY STATEMENTS:

P211: DO NOT SPRAY ON AN OPEN FLAME OR OTHER IGNITION SOURCE.

P220: KEEP/STORE AWAY FROM CLOTHING/.../COMBUSTIBLE MATERIALS.

P235: KEEP COOL.

P251:

PRESSURIZED CONTAINER: DO NOT PIERCE OR BURN, EVEN AFTER USE.

P375: FIGHT FIRE REMOTELY DUE TO THE RISK OF EXPLOSION.

P102: KEEP OUT OF REACH OF CHILDREN.

P103: READ LABEL BEFORE USE.

P202:

DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD.

P234: KEEP ONLY IN ORIGINAL CONTAINER.

P260: DO NOT BREATHE DUST/FUME/GAS/MIST/VAPOURS/SPRAY.

P261: AVOID BREATHING DUST/FUME/GAS/MIST/VAPOURS/SPRAY.

P262: DO NOT GET IN EYES, ON SKIN, OR ON CLOTHING.

P264: WASH ... THOROUGHLY AFTER HANDLING.

P270: DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.

P271: USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.

P273: AVOID RELEASE TO THE ENVIRONMENT.

P280:

WEAR PROTECTIVE GLOVES/PROTECTIVE CLOTHING/EYE PROTECTION/FACE PROTECTION.

P281: USE PERSONAL PROTECTIVE EQUIPMENT AS REQUIRED.

P285: IN CASE OF INADEQUATE VENTILATION WEAR RESPIRATORY PROTECTION.

P312: CALL A POISON CENTER OR DOCTOR/PHYSICIAN IF YOU FEEL UNWELL.

P351: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES.

P374: FIGHT FIRE WITH NORMAL PRECAUTIONS FROM A REASONABLE DISTANCE.

P402: STORE IN A DRY PLACE.

P210: KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT SURFACES. - NO SMOKING.

P410+P412:

PROTECT FROM SUNLIGHT. DO NOT EXPOSE TO TEMPERATURES EXCEEDING
50 DEG. C / 122 DEG. F.

P240: GROUND/BOND CONTAINER AND RECEIVING EQUIPMENT.

P241: USE EXPLOSION-PROOF ELECTRICAL/VENTILATING/LIGHTING/.../ EQUIPMENT.

P242: USE ONLY NON-SPARKING TOOLS.

P243: TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGE.

P303+P361+P353:
IF ON SKIN (OR HAIR):
REMOVE/TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH
WATER/SHOWER.

P370+P378:
IN CASE OF FIRE: USE ... FOR EXTINCTION.

P403+P235: STORE IN A WELL-VENTILATED PLACE. KEEP COOL.

P501: DISPOSE OF CONTENTS/CONTAINER TO ...

P321: SPECIFIC TREATMENT (SEE ... ON THIS LABEL).

P352: WASH WITH PLENTY OF SOAP AND WATER.

P362: TAKE OFF CONTAMINATED CLOTHING AND WASH BEFORE REUSE.

P332+P313:
IF SKIN IRRITATION OCCURS: GET MEDICAL ADVICE/ATTENTION.

P305+P351+P338:
IF IN EYES:
RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF
PRESENT AND EASY TO DO. CONTINUE RINSING.

P337+P313:
IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ATTENTION.

P304+P340:
IF INHALED:
REMOVE VICTIM TO FRESH AIR AND KEEP AT REST IN A POSITION COMFORTABLE FOR
BREATHING.

P405: STORE LOCKED UP.

P403+P233: STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED.

P302+P350:
IF ON SKIN: GENTLY WASH WITH PLENTY OF SOAP AND WATER.

3. COMPOSITION/INFORMATION ON INGREDIENTS

 top

HAZARDOUS SUBSTANCES:

CHEMICAL NAME	CAS-NO.	WT.% RANGE	GHS SYMBOLS	GHS STATEMENTS
LIQUEFIED PETROLEUM GAS	68476-86-8	25-50		
LIMESTONE	1317-65-3	2.5-10		
ALIPHATIC HYDROCARBON	64742-89-8	2.5-10		
XYLENE	1330-20-7	2.5-10	GHS02	H226
BARIUM SULFATE	7727-43-7	2.5-10		
HYDROTREATED LIGHT DISTILLATE	64742-47-8	2.5-10	GHS06	H331
MINERAL SPIRITS	64742-88-7	1.0-2.5	GHS06	H331
ETHYLBENZENE	100-41-4	1.0-2.5	GHS02-GHS07	H225-332

THE TEXT FOR GHS HAZARD STATEMENTS SHOWN ABOVE (IF ANY) IS GIVEN IN THE
"16. OTHER INFORMATION" SECTION.

4. FIRST-AID MEASURES



FIRST AID - EYE CONTACT:

IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. DO NOT ALLOW RUBBING OF EYES OR KEEPING EYES CLOSED.

FIRST AID - SKIN CONTACT:

WASH SKIN WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS OR PERSISTS.

FIRST AID - INHALATION:

IF YOU EXPERIENCE DIFFICULTY IN BREATHING, LEAVE THE AREA TO OBTAIN FRESH AIR. IF CONTINUED DIFFICULTY IS EXPERIENCED, GET MEDICAL ASSISTANCE IMMEDIATELY. REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. GET IMMEDIATE MEDICAL ATTENTION. DO NOT USE MOUTH-TO-MOUTH RESUSCITATION.

FIRST AID - INGESTION:

ASPIRATION HAZARD:

DO NOT INDUCE VOMITING OR GIVE ANYTHING BY MOUTH BECAUSE THIS MATERIAL CAN ENTER THE LUNGS AND CAUSE SEVERE LUNG DAMAGE. GET IMMEDIATE MEDICAL ATTENTION. IF SWALLOWED, GET MEDICAL ATTENTION.

5. FIRE-FIGHTING MEASURES



EXTINGUISHING MEDIA:

ALCOHOL FILM FORMING FOAM, CARBON DIOXIDE, DRY CHEMICAL, DRY SAND, WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS:

FLASH POINT IS LESS THAN 20 DEG. F. - EXTREMELY FLAMMABLE LIQUID AND VAPOR!

WATER SPRAY MAY BE INEFFECTIVE. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. VAPORS MAY FORM EXPLOSIVE MIXTURES WITH AIR. VAPORS CAN TRAVEL TO A SOURCE OF IGNITION AND FLASH BACK. KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. PERFORATION OF THE PRESSURIZED CONTAINER MAY CAUSE BURSTING OF THE CAN. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT DUE TO BUILDUP OF STEAM. NO UNUSUAL FIRE OR EXPLOSION HAZARDS NOTED.

SPECIAL FIREFIGHTING PROCEDURES:

EVACUATE AREA AND FIGHT FIRE FROM A SAFE DISTANCE. FULL PROTECTIVE EQUIPMENT INCLUDING SELF-CONTAINED BREATHING APPARATUS SHOULD BE USED. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILDUP AND POSSIBLE AUTOIGNITION OR EXPLOSION. USE WATER SPRAY TO KEEP FIRE-EXPOSED CONTAINERS COOL. CONTAINERS MAY EXPLODE WHEN HEATED.

6. ACCIDENTAL RELEASE MEASURES



STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. REMOVE ALL SOURCES OF IGNITION, VENTILATE AREA AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS. DISPOSE OF ACCORDING TO LOCAL, STATE (PROVINCIAL) AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS. ISOLATE THE HAZARD AREA AND DENY ENTRY TO UNNECESSARY AND UNPROTECTED PERSONNEL. VENTILATE AREA, ISOLATE SPILLED MATERIAL, AND REMOVE WITH INERT ABSORBENT. DISPOSE OF CONTAMINATED ABSORBENT, CONTAINER, AND UNUSED CONTENTS IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

7. HANDLING AND STORAGE**HANDLING:**

WASH THOROUGHLY AFTER HANDLING. WASH HANDS BEFORE EATING. USE ONLY IN A WELL-VENTILATED AREA. FOLLOW ALL MSDS/LABEL PRECAUTIONS EVEN AFTER CONTAINER IS EMPTIED BECAUSE IT MAY RETAIN PRODUCT RESIDUES. AVOID BREATHING FUMES, VAPORS, OR MIST. REMOVE CONTAMINATED CLOTHING AND LAUNDRER BEFORE REUSE. USE ONLY WITH ADEQUATE VENTILATION. AVOID CONTACT WITH EYES, SKIN AND CLOTHING.

STORAGE:

KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. CONTENTS UNDER PRESSURE. DO NOT STORE ABOVE 120 DEG. F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS I FLAMMABLE LIQUIDS. CONTENTS UNDER PRESSURE. DO NOT EXPOSE TO HEAT OR STORE ABOVE 120 DEG. F. PRODUCT SHOULD BE STORED IN TIGHTLY SEALED CONTAINERS AND PROTECTED FROM HEAT, MOISTURE, AND FOREIGN MATERIALS. STORE IN A DRY, WELL VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. KEEP AWAY FROM HEAT, SPARKS, FLAME AND SOURCES OF IGNITION. AVOID EXCESS HEAT.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CHEMICAL NAME	CAS-NO.	WEIGHT % LESS THAN
LIQUEFIED PETROLEUM GAS	68476-86-8	30.0
LIMESTONE	1317-65-3	10.0
ALIPHATIC HYDROCARBON	64742-89-8	10.0
XYLENE	1330-20-7	5.0
BARIUM SULFATE	7727-43-7	5.0
HYDROTREATED LIGHT DISTILLATE	64742-47-8	5.0
MINERAL SPIRITS	64742-88-7	5.0
ETHYLBENZENE	100-41-4	5.0

CHEMICAL NAME	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL-CEILING
LIQUEFIED PETROLEUM GAS	N.E.	N.E.	N.E.	N.E.
LIMESTONE	N.E.	N.E.	15 MG/M3 [TOTAL DUST]	N.E.
ALIPHATIC HYDROCARBON	100 PPM	N.E.	100 PPM	N.E.
XYLENE	100 PPM	150 PPM	100 PPM	N.E.
BARIUM SULFATE	10 MG/M3	N.E.	15 MG/M3 [TOTAL DUST]	N.E.
HYDROTREATED LIGHT DISTILLATE	200 MG/M3	N.E.	N.E.	N.E.
MINERAL SPIRITS	100 PPM	N.E.	100 PPM	N.E.
ETHYLBENZENE	20 PPM	125 PPM	100 PPM	N.E.

PERSONAL PROTECTION:

ENGINEERING CONTROLS:

USE PROCESS ENCLOSURES, LOCAL EXHAUST VENTILATION, OR OTHER ENGINEERING CONTROLS TO CONTROL AIRBORNE LEVELS BELOW RECOMMENDED EXPOSURE LIMITS. USE EXPLOSION-PROOF VENTILATION EQUIPMENT. PREVENT BUILD-UP OF VAPORS BY OPENING ALL DOORS AND WINDOWS TO ACHIEVE CROSS-VENTILATION. PROVIDE GENERAL DILUTION OF LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP TLV OF HAZARDOUS INGREDIENTS BELOW ACCEPTABLE LIMITS.

RESPIRATORY PROTECTION:

A RESPIRATORY PROTECTION PROGRAM THAT MEETS OSHA 1910.134 AND ANSI Z88.2 REQUIREMENTS MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT A RESPIRATOR'S USE. A NIOSH/MSHA APPROVED AIR PURIFYING RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE OR CANISTER MAY BE PERMISSIBLE UNDER CERTAIN CIRCUMSTANCES WHERE AIRBORNE CONCENTRATIONS ARE EXPECTED TO EXCEED EXPOSURE LIMITS.

SKIN PROTECTION:

USE IMPERVIOUS GLOVES TO PREVENT SKIN CONTACT AND ABSORPTION OF THIS MATERIAL THROUGH THE SKIN. NITRILE OR NEOPRENE GLOVES MAY AFFORD ADEQUATE SKIN PROTECTION. USE GLOVES TO PREVENT PROLONGED SKIN CONTACT.

EYE PROTECTION:

USE SAFETY EYEWEAR DESIGNED TO PROTECT AGAINST SPLASH OF LIQUIDS.

OTHER PROTECTIVE EQUIPMENT:

REFER TO SAFETY SUPERVISOR OR INDUSTRIAL HYGIENIST FOR FURTHER INFORMATION REGARDING PERSONAL PROTECTIVE EQUIPMENT AND ITS APPLICATION. REFER TO SAFETY SUPERVISOR OR INDUSTRIAL HYGIENIST FOR FURTHER GUIDANCE REGARDING TYPES OF PERSONAL PROTECTIVE EQUIPMENT AND THEIR APPLICATIONS.

HYGIENIC PRACTICES:

WASH THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING OR SMOKING. REMOVE CONTAMINATED CLOTHING IMMEDIATELY AND LAUNDRY BEFORE REUSE.

9. PHYSICAL AND CHEMICAL PROPERTIES top

APPEARANCE: AEROSOLIZED MIST

PHYSICAL STATE: LIQUID

ODOR: MILD

ODOR THRESHOLD: N.E.

RELATIVE DENSITY: 0.846

PH: N.D.

FREEZE POINT, DEG. C: N.D.

VISCOSITY: N.D.

SOLUBILITY IN WATER: MISCIBLE

PARTITION COEFFICIENT, N-OCTANOL/WATER: NO INFORMATION

DECOMPOSITION TEMP., DEG. C: NO INFORMATION

BOILING RANGE, DEG. C: -34 - 415

EXPLOSIVE LIMITS, VOL%: 0.9 - 12.6

FLAMMABILITY: SUPPORTS COMBUSTION

FLASH POINT, DEG. C: -105

EVAPORATION RATE: FASTER THAN ETHER

AUTO-IGNITION TEMP., DEG. C: NO INFORMATION

VAPOR DENSITY: HEAVIER THAN AIR

VAPOR PRESSURE: N.D.

(SEE "OTHER INFORMATION" SECTION FOR ABBREVIATION LEGEND)

10. STABILITY AND REACTIVITY

 top

CONDITIONS TO AVOID:

AVOID TEMPERATURES ABOVE 120 DEG. F. AVOID ALL POSSIBLE SOURCES OF IGNITION. AVOID CONTACT WITH STRONG ACID AND STRONG BASES.

INCOMPATIBILITY:

INCOMPATIBLE WITH STRONG OXIDIZING AGENTS, STRONG ACIDS AND STRONG ALKALIES.

HAZARDOUS DECOMPOSITION:

BY OPEN FLAME, CARBON MONOXIDE AND CARBON DIOXIDE. WHEN HEATED TO DECOMPOSITION, IT EMITS ACRID SMOKE AND IRRITATING FUMES. CONTAINS SOLVENTS WHICH MAY FORM CARBON MONOXIDE, CARBON DIOXIDE, AND FORMALDEHYDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR UNDER NORMAL CONDITIONS.

STABILITY: THIS PRODUCT IS STABLE UNDER NORMAL STORAGE CONDITIONS.

11. TOXICOLOGICAL INFORMATION

 top

EFFECTS OF OVEREXPOSURE - EYE CONTACT: CAUSES SERIOUS EYE IRRITATION

EFFECTS OF OVEREXPOSURE - SKIN CONTACT:

SUBSTANCE MAY CAUSE SLIGHT SKIN IRRITATION. PROLONGED OR REPEATED CONTACT MAY CAUSE SKIN IRRITATION. MAY CAUSE SKIN IRRITATION. ALLERGIC REACTIONS ARE POSSIBLE.

EFFECTS OF OVEREXPOSURE - INHALATION:

HARMFUL IF INHALED. HIGH GAS, VAPOR, MIST OR DUST CONCENTRATIONS MAY BE HARMFUL IF INHALED. AVOID BREATHING FUMES, SPRAY, VAPORS, OR MIST. HIGH VAPOR CONCENTRATIONS ARE IRRITATING TO THE EYES, NOSE, THROAT AND LUNGS. PROLONGED OR EXCESSIVE INHALATION MAY CAUSE RESPIRATORY TRACT IRRITATION.

EFFECTS OF OVEREXPOSURE - INGESTION:

ASPIRATION HAZARD IF SWALLOWED; CAN ENTER LUNGS AND CAUSE DAMAGE. HARMFUL IF SWALLOWED.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:

IARC LISTS ETHYLBENZENE AS A POSSIBLE HUMAN CARCINOGEN (GROUP 2B). OVEREXPOSURE TO XYLENE IN LABORATORY ANIMALS HAS BEEN ASSOCIATED WITH LIVER ABNORMALITIES, KIDNEY, LUNG, SPLEEN, EYE AND BLOOD DAMAGE AS WELL AS REPRODUCTIVE DISORDERS. EFFECTS IN HUMANS, DUE TO CHRONIC OVEREXPOSURE, HAVE INCLUDED LIVER, CARDIAC ABNORMALITIES AND NERVOUS SYSTEM DAMAGE. MAY CAUSE CENTRAL NERVOUS SYSTEM DISORDER (E.G., NARCOSIS INVOLVING A LOSS OF COORDINATION, WEAKNESS, FATIGUE, MENTAL CONFUSION, AND BLURRED VISION) AND/OR DAMAGE. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. HIGH CONCENTRATIONS MAY LEAD TO CENTRAL NERVOUS SYSTEM EFFECTS (DROWSINESS, DIZZINESS, NAUSEA, HEADACHES, PARALYSIS, AND BLURRED VISION) AND/OR DAMAGE.

PRIMARY ROUTE(S) OF ENTRY:

EYE CONTACT, INGESTION, INHALATION, SKIN ABSORPTION, SKIN CONTACT

ACUTE TOXICITY VALUES:

THE ACUTE EFFECTS OF THIS PRODUCT HAVE NOT BEEN TESTED. DATA ON INDIVIDUAL COMPONENTS ARE TABULATED BELOW:

CAS-NO.	CHEMICAL NAME	ORAL LD50	DERMAL LD50	VAPOR LC50
64742-89-8	ALIPHATIC HYDROCARBON	N.I.	3000 MG/KG RABBIT	N.I.
1330-20-7	XYLENE	4300 MG/KG RAT	N.I.	47635 MG/L RAT
64742-47-8	HYDROTREATED LIGHT DISTILLATE	>5000 MG/KG RAT	>2000 MG/KG RABBIT	>5.2 MG/L RAT
64742-88-7	MINERAL SPIRITS	>5000 MG/KG RAT	3000 MG/KG RABBIT	>5.28 MG/L RAT
100-41-4	ETHYLBENZENE	3500 MG/KG RAT	15354 MG/KG RABBIT	17.2 MG/L RAT

N.I. - NO INFORMATION

12. ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION:

PRODUCT IS A MIXTURE OF LISTED COMPONENTS. PRODUCT IS A MIXTURE OF LISTED COMPONENTS.

13. DISPOSAL INFORMATION

DISPOSAL INFORMATION:

DISPOSE OF MATERIAL IN ACCORDANCE TO LOCAL, STATE, AND FEDERAL REGULATIONS AND ORDINANCES. DO NOT ALLOW TO ENTER WATERWAYS, WASTEWATER, SOIL, STORM DRAINS OR SEWER SYSTEMS.

14. TRANSPORT INFORMATION

	DOMESTIC (USDOT)	INTERNATIONAL (IMDG)	AIR (IATA)	TDG (CANADA)
UN NUMBER	N.A.	1950	1950	N.A.
PROPER SHIPPING NAME	PAINT PRODUCTS IN LIMITED QUANTITIES	AEROSOLS	AEROSOLS	PAINT PRODUCTS IN LIMITED QUANTITIES
HAZARD CLASS	N.A.	2.1	2.1	N.A.
PACKING GROUP	N.A.	N.A.	N.A.	N.A.
LIMITED QUANTITY	YES	YES	YES	YES

15. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

CERCLA - SARA HAZARD CATEGORY:

THIS PRODUCT HAS BEEN REVIEWED ACCORDING TO THE EPA 'HAZARD CATEGORIES' PROMULGATED UNDER SECTIONS 311 AND 312 OF THE SUPERFUND AMENDMENT AND

REAUTHORIZATION ACT OF 1986 (SARA TITLE III) AND IS CONSIDERED, UNDER APPLICABLE DEFINITIONS, TO MEET THE FOLLOWING CATEGORIES:
FIRE HAZARD, PRESSURE HAZARD, ACUTE HEALTH HAZARD, CHRONIC HEALTH HAZARD

SARA SECTION 313:

THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372:

CHEMICAL NAME	CAS-NO.
XYLENE	1330-20-7
ETHYLBENZENE	100-41-4

TOXIC SUBSTANCES CONTROL ACT:

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF TSCA 12(B) IF EXPORTED FROM THE UNITED STATES:

CHEMICAL NAME	CAS-NO.
ACETALDEHYDE	75-07-0

INVENTORY INFORMATION:

COUNTRY	VALUE
USA (TSCA)	NO INFORMATION
CANADA (DSL)	NO INFORMATION
MEXICO (INSQ)	NO INFORMATION
EUROPE (EINECS)	NO INFORMATION
JAPAN (ENCS)	NO INFORMATION
PHILIPPINES (PICCS)	NO INFORMATION
CHINA (IECSC)	NO INFORMATION
AUSTRALIA (AICS)	NO INFORMATION
KOREA (KECI)	NO INFORMATION
NEW ZEALAND (NZIOC)	NO INFORMATION

NO INFORMATION

CALIFORNIA PROPOSITION 65:

WARNING:

THIS PRODUCTS CONTAINS A SUBSTANCE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

CHEMICAL NAME	CAS-NO.
ETHYLBENZENE	100-41-4

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS:

WARNING:

THIS PRODUCT CONTAINS A SUBSTANCE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

NO PROPOSITION 65 REPRODUCTIVE TOXINS EXIST IN THIS PRODUCT.

INTERNATIONAL REGULATIONS:

CANADIAN WHMIS:

THIS SDS HAS BEEN PREPARED IN COMPLIANCE WITH CONTROLLED PRODUCT REGULATIONS EXCEPT FOR THE USE OF THE 16 HEADINGS.

16. OTHER INFORMATION



HMIS RATINGS:

HEALTH 2*
FLAMMABILITY 4
PHYSICAL HAZARD 0
PERSONAL PROTECTION X

CANADIAN WHMIS CLASS:

B2
D2A

NFPA RATINGS:

HEALTH 2
FLAMMABILITY 4
INSTABILITY 0

VOLATILE ORGANIC COMPOUNDS, G/L: 551

MSDS REVISION DATE: 8/26/2014

REASON FOR REVISION: NO INFORMATION

LEGEND:

N.A. - NOT APPLICABLE
N.E. - NOT ESTABLISHED
N.D. - NOT DETERMINED

TEXT FOR GHS HAZARD STATEMENTS SHOWN IN SECTION 3 DESCRIBING EACH INGREDIENT:

H225: HIGHLY FLAMMABLE LIQUID AND VAPOUR.
H226: FLAMMABLE LIQUID AND VAPOUR.
H331: TOXIC IF INHALED.
H332: HARMFUL IF INHALED.

ICONS FOR GHS PICTOGRAMS SHOWN IN SECTION 3 DESCRIBING EACH INGREDIENT:

GHS02: FLAME
GHS06: SKULLS AND CROSSBONES
GHS07: EXCLAMATION MARK

RUST-OLEUM CORPORATION BELIEVES, TO THE BEST OF ITS KNOWLEDGE, INFORMATION AND BELIEF, THE INFORMATION CONTAINED HEREIN TO BE ACCURATE AND RELIABLE AS OF THE DATE OF THIS SAFETY DATA SHEET. HOWEVER, BECAUSE THE CONDITIONS OF HANDLING, USE, AND STORAGE OF THESE MATERIALS ARE BEYOND OUR CONTROL, WE ASSUME NO RESPONSIBILITY OR LIABILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE INCURRED BY THE USE OF THESE MATERIALS. RUST-OLEUM CORPORATION MAKES NO WARRANTY, EXPRESSED OR IMPLIED, REGARDING THE ACCURACY OR RELIABILITY OF THE DATA OR RESULTS OBTAINED FROM THEIR USE. ALL MATERIALS MAY PRESENT UNKNOWN HAZARDS AND SHOULD BE USED WITH CAUTION. THE INFORMATION AND RECOMMENDATIONS IN THIS MATERIAL SAFETY DATA SHEET ARE OFFERED FOR THE USERS' CONSIDERATION AND EXAMINATION. IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE FINAL SUITABILITY OF THIS INFORMATION AND TO COMPLY WITH ALL APPLICABLE INTERNATIONAL, FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS.